



TAT YIN (HK) CO., LTD.

TufGuard AC

High Performance Liquid Applied Acrylic Waterproofing System

2024022

DESCRIPTION

TufGuard AC is a single pack, high build, flexible, elastomeric waterproof coating based on weather resistant pigments, fillers and styrene acrylic ester resins. It allows concrete to breathe whilst maintaining waterproofing characteristics, has excellent bond strength and fills and bridges hairline cracks. The cured membrane provides excellent resistance to carbonation and prevents chloride ion ingress.



ADVANTAGE

- Waterproof, weatherproof, excellent UV resistance.
- High build coating helps mask surface imperfections in concrete.
- Excellent bond strength.
- Seamless & flexible for bridging hairline cracks.
- Solar reflective.
- Single component. Easy to apply by brush, roller or airless spray.



USAGE

- Used as an external and internal coating for concrete and masonry.
- Used as an anti-carbonation coating.
- Used as a protective coating for sea walls and coastal environments.

SPECIFICATION COMPLIANCE

- ASTM D2370
- ASTM C1202:2005
- ASTM E 96

PHYSICAL & MECHANICAL PROPERTIES

Property	Typical Results
Appearance	Grey thick paste
Specific gravity @ 25 °C	~1.25
Reduction in chloride ion penetration	≥ 97%
Reduction in water absorption	≥95%
Water vapour transmission	< 1 Perm
Chemical Resistance	Resistant to spillage of gasoline, diesel, sewage, weak acids and alkalis

APPLICATION INSTRUCTIONS

Surface Preparation : Ensure that surfaces are clean, sound, stable and free of dirt, dust, grease and any other contaminants. Remove any traces of algae and fungal growth with a wire brush, treat with a fungicide solution and wash down with clean water. Old concrete may require grit blasting to remove old coatings or membranes. New concrete can be coated once the initial water-curing period is over (approx. 7 days).

Cleaning : Wash tools with water immediately after use. If product has set, remove with a knife and immerse in water.

Watchpoint : Do not apply **TufGuard AC** when rain is likely as full resistance is only achieved in the fully cured state.

Application : Apply **TufGuard AC** onto the surface in one direction taking care not to be scrub the material or brush unevenly. Allow to dry and inspect for imperfections that should be made good prior to application of second or any subsequent coats. Apply second (and any subsequent coats) at right angles to the previous coats.



TufGuard AC

High Performance Liquid Applied Acrylic Waterproofing System

202402

COVERAGE

Consumption of TufGuard AC will be around 4 to 5 m²/litre @ 200 micron DFT depending on the substrate's texture, porosity, ambient temperature, etc.

STORAGE

It has a shelf life of 12 months provided it is stored under cover, out of direct sunlight.

PACKAGING

20 Litre drum.

HEALTH & SAFETY

TufGuard AC does not fall into the hazard classifications of current regulations. However, it should not be swallowed or allowed to come into contact with skin and eyes. Suitable protective gloves and goggles should be worn. Splashes on the skin should be removed with water. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. If swallowed seek medical attention immediately- do not induce vomiting.



Please enquire about our range of construction product

The information and the recommendations relating to the application and end use of this product are given in good faith and are based on the information provided by the manufacturer of the product and/or the Company's current knowledge and experience in connection with the product when properly stored, handled and applied under normal conditions and no liability for final function at the job site is assumed. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written and/or oral recommendations, or from any other advice offered by the Company. No responsibility or Liability by the Company will be accepted for misuse, misreading or derivation from the recommended guidelines in respect of this product and the user shall determine the suitability of the product for his intended use and all risks and liability in connection therewith. The information contained in this brochure may change at any time without notice.

Room 1504, 15/F, Emperor Group Centre, No. 288 Hennessy Road, Wanchai, Hong Kong

Tel: 2121 4694

E-mail: sales@tyl.com.hk

Fax: 3020 6789

Website: www.tatynltd.com