



## TYL<sup>®</sup> - Cell 470

Bitumen Impregnated Fiber Board Joint Filler

202402

### DESCRIPTION

TYL<sup>®</sup>-CELL 470 is compressible, non-extruding, bitumen impregnated fiber board joint filler for use in forming joints between in-situ and pre-cast concrete components. The density is 275kg/m<sup>3</sup>.

### USES

- Regulate depth of sealant application.
- Isolation layer between concrete structures.
- Forming structure expansion and separation joints.

### APPLICATION INSTRUCTIONS

When used as an expansion or isolation joint filler in brickwork and concrete, TYL<sup>®</sup>-Cell 470 should be positioned to provide for a surface sealing slot of the required dimension ensuring that the sealing slot is free from mortar droppings or slurry bridging.

TYL<sup>®</sup>-Cell 470 should be fixed into position using a suitable contact adhesive (such as TYL<sup>®</sup>-BituProof / Dunlop LP) ensuring that the sealing slot is not contaminated with adhesive



### ADVANTAGES

- Readily compressible.
- Easy to apply
- Will not extrude under compression
- Resilient

### PACKAGING

Sheet thickness :	9, 12, 18, 20, and 25mm
Sheet size :	4' x 7'

### LIMITATIONS

TYL-Cell 470 will burn on contact with fire directly.

### STORAGE

It should be stored in the dry and not left exposed to the elements for

### **Please enquire about our range of construction product**

The information and the recommendations relating to the application and end use if this product are given in good faith and are based on the information provided by the manufacturer of the product and/or the Company's current knowledge and experience in connection with the product when properly stored, handled and applied under normal conditions and no liability if final function at the job site is assumed. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written and/or oral recommendations, or from any other advice offered by the Company. No responsibility or Liability by the Company will be accepted for misuse, misreading or derivation from the recommended guidelines in respect of this product and the user shall determine the suitability of the product for his intended use and all risks and liability in connection therewith. The information contained in this brochure may change at any time without notice.